

Accu Sync™

Gain unparalleled pressure regulation for any Hunter valve.

Operating Specifications:

- Regulation from 1.4 to 7.0 bar; 140 to 700 kPa
- Static pressure: 10 bar; 1,000 kPa
- Required dynamic pressure differential: 1.0 bar; 100 kPa
- Works with AC- and DC-latching solenoids
- Works with any Hunter valve
- Warranty period: 2 years



Accu-Sync Valve Recommended Flow Range

| Valve | Flow | |
|-------------|--------------------|-----------|
| | m ³ /hr | l/min |
| SRV-100 | 19 - 114 | 1.2 - 6.8 |
| PGV-100/101 | 19 - 114 | 1.2 - 6.8 |
| PGV-151 | 75 - 454 | 4.5 - 28 |
| PGV-201 | 150 - 750 | 9.0 - 34 |
| ICV-101 | 19 - 150 | 1.2 - 9.0 |
| ICV-151 | 75 - 510 | 4.5 - 31 |
| ICV-201 | 150 - 560 | 9.0 - 34 |
| ICV-301 | 565 - 1135 | 34 - 68 |
| IBV-101 | 19 - 150 | 1.2 - 9.0 |
| IBV-151 | 75 - 510 | 4.5 - 31 |
| IBV-201 | 150 - 560 | 9.0 - 34 |
| IBV-301 | 565 - 1135 | 34 - 68 |

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://redesign.hunterindustries.com/en-metric/irrigation-product/valves/accu-synctm>
052424