

## Eco-Wrap®

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

### KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20 to 40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximizing efficiency
- Check height of 6' minimizes system drainage and runoff



### Operating Specifications

- Flow rate: 0.6 GPH
- Emitter spacing: 12"
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 250'
- Accepts 17 mm barb or LOC fittings
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

### Product Specifications

- Operating range: 15 to 50 PSI
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 6'
- Recommended installation depth: turf (4" to 6"); other (4" to 8")
- Compatible with Eco-Mat

#### ECO-WRAP TECHNICAL SPECIFICATIONS

##### 17mm

Flow	0.6 GPH
Roll Length	250'
Operating Pressure	15-50 PSI
Minimum Filtration	120 mesh/125 micron
Emitter Spacing	12"

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://redesign.hunterindustries.com/irrigation-product/micro-irrigation/eco-wrap>

