

Root Zone Watering System

Deliver water across all levels of the root zone for high-efficiency subsurface irrigation of trees and shrubs.

KEY BENEFITS

- Patented StrataRoot™ baffles divert water to all levels of the root zone while adding strength to the unit
- Durable locking cap for vandal resistance
- Pressure-compensating bubbler for accurate water flow
- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Preassembled for fast installation

OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.25 or 0.50 GPM
- Recommended pressure range: 15 to 70 PSI
- Warranty period: 2 years

FACTORY-INSTALLED OPTIONS

- Check valve (HCV)
- Locking reclaimed water purple cap

USER-INSTALLED OPTIONS

- Fabric sleeve to prevent soil intrusion in sandy areas for 18" and 36" models P/N: RZWS-SLEEVE
- Replacement cap for 18" and 36" models P/N: 913300SP
- Locking reclaimed purple cap for 18" and 36" models P/N: 913301SP
- Reclaimed water purple cap for 10" model P/N: RZWS10-RCC



Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://redesign.hunterindustries.com/irrigation-product/micro-irrigation/root-zone-watering-system>
041224