



**DETAIL LEGEND:**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>① TTS800-DD POP-UP ROTOR, 2-STATION DECODER</li> <li>② TTS800-E POP-UP ROTOR, ELECTRIC VALVE-IN-HEAD</li> <li>③ DECODER/SOLENOID ASSEMBLY INSIDE TTS COMPARTMENT</li> <li>④ HUNTER SWING JOINT ASSEMBLY (HSJ). INSTALL SWING JOINT LAY ARM AT 30°- 45° ANGLE TO THE LATERAL LINE.</li> <li>⑤ LATERAL LINE FITTING PER PLAN.</li> </ul> | <ul style="list-style-type: none"> <li>⑥ LATERAL LINE PER PLAN. SOIL DEPTH PER PLAN.</li> <li>⑦ 1½" [40 mm] MALE ACME</li> <li>⑧ HUNTER TWO-WIRE CABLE</li> <li>⑨ WIRE SPLICE IN TTS COMPARTMENT</li> <li>⑩ TWO-WIRE PATH</li> <li>⑪ CONTROL WIRE TO SECOND ROTOR HEAD</li> <li>⑫ DECODER WIRE</li> <li>⑬ FINISHED GRADE</li> </ul> |
|---|---|

**TTS-800-DD 2-STATION DECODER  
VALVE-IN-HEAD ROTOR WITH ADJACENT TTS-800-E**

