

# NODE-BT

Manage gardens, greenhouses, traffic medians, and temporary irrigation sites from a smartphone without opening the valve box.

## KEY BENEFITS

- Number of stations:
  - 1, 2, or 4 (fixed models)
- Bluetooth® battery-operated controller for automatic irrigation
- Active station LEDs and battery-life LED indicator for replacement
- 3 programs with 8 start times each and 1 second to 12-hour run times
- Suspend irrigation up to 99 days during the off-season
- Manual push-button operation for quick operation without a smartphone
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Monthly and global seasonal adjustment for quicker schedule adjustments without changing run times

## OPERATING SPECIFICATIONS

- One or two 9 V alkaline batteries
- Operates Hunter DC-Latching Solenoids
- 100' maximum wire runs, 18 AWG wire only
- Station output: 9 to 11 VDC
- P/MV output: 9 to 11 VDC (multi-station models)
- Sensor inputs: 2 (wired soil plus wired rain, freeze, or wind only)
- Bluetooth 5.0 (BLE)
- Approvals: IP68 (submersible), UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years

## APP SPECIFICATIONS

- iOS® 9.0 or above, Android™ 5.0 or above
- Maximum communication distance: 50'
- See all app features at [hunter.info/NodeBT](http://hunter.info/NodeBT)

NODE-BT	
Model	Description
NODE-BT-100	Single-station Bluetooth battery controller and DC-Latching Solenoid
NODE-BT-100-LS	Single-station Bluetooth battery controller
NODE-BT-100-VALVE	Single-station Bluetooth battery controller with PGV-101G valve and DC-Latching Solenoid (NPT threads)
NODE-BT-200	2-station Bluetooth battery controller
NODE-BT-400	4-station Bluetooth battery controller

USER-INSTALLED OPTIONS	
Model	Description
SC-PROBE	Soil probe for moisture sensing
SP-NODE-BT	Solar Panel Kit for NODE-BT Controllers
458200	DC-Latching Solenoid (for all Hunter valves)

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc., and any use of such marks by Hunter Industries is under license. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries, and is used under license. Android is a trademark of Google LLC.



**NODE-BT**  
Height: 3"  
Diameter: 3½"




**SC-PROBE**  
Soil Moisture Sensor (optional)  
Height: 3¼"  
Diameter: 1"



**SP-NODE-BT**  
NODE-BT Solar Panel  
Height: 1¾"  
Width: 3"  
Depth: 9½"

## NODE-BT WITH PGV INSTALLATION



Compatible with:



**Mini-Clik®  
Sensor**



**Waterproof Wire  
Connector**