

FILTERS & FILTER REGULATORS

Choose rugged filters and filter regulators with stainless steel screens for maximum performance.

KEY BENEFITS

- HFR-075 (Hunter Filter Regulator)
 - Compact, all-in-one filter and regulator minimise required valve box space
 - Senninger regulator provides precise regulation to protect system from high pressure
 - 150 mesh (100 microns) stainless steel screen for years of reliable filtration
 - Wide flow range covers most drip applications
- HY-075 (Hunter Y-Filter)
 - 150 mesh (100 microns) stainless steel screen for years of reliable filtration
 - Wide flow range covers most drip applications

OPERATING SPECIFICATIONS

- HFR-075
 - Pressure regulation: 1.7 or 2.8 bar; 170 or 280 kPa
 - Flow: 2 to 55 l/min
 - Operating pressure: 1.4 to 8.0 bar; 140 to 800 kPa
 - Operating temperature: up to 66°C
- HY-075
 - Flow: up to 75 l/min
 - Operating pressure: up to 8.0 bar; 800 kPa
 - Operating temperature: up to 66°C
- Warranty period: 2 years



HFR-075-25

HFR-075-40

Height: 18 cm
Width: 7 cm
Length: 16 cm
3/4" inlet x 3/4" outlet



HY-075

Height: 15 cm
Width: 7 cm
Length: 13 cm

HUNTER FILTERS

Model	Description
HFR-075-25	Filter regulator, 3/4" inlet/outlet, 1.7 bar; 170 kPa
HFR-075-40	Filter regulator, 3/4" inlet/outlet, 2.8 bar; 280 kPa
HY-075	3/4" filter with 3/4" inlet/outlet

PCZ-101 installed in a Multi-Purpose Box

