

X2™

This online-capable controller offers rapid schedule programming and advanced water-saving features.

KEY BENEFITS

- Number of stations:
 - 4, 6, 8, or 14 (fixed models)
- Wi-Fi capable controller automatically managed by Hydrawise® Software
- Backlit display provides optimal visibility in any light
- Three flexible programs with four start times each and up to 6-hour run times
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Hide Programs option shows one program and one start time for simplification
- Suspend irrigation up to 99 days during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve™ Memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule updates without changing run times

WI-FI MODULE BENEFITS

- Provides online irrigation management with controller status and faulty wiring alerts
- Standard ABC programming allows for three independent programs with six start times per program and 24-hour maximum run times
- Predictive Watering™ provides precise weather adjustments for maximum water savings
- Compatibility with Amazon Alexa™, Control4®, and HomeSeer™
- See complete WAND Wi-Fi Module benefits and specifications on [page 113](#)

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals (controller): Plastic IP55 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Approvals (module): Wi-Fi b/g/n, Bluetooth® 5.0, UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years



X2
Height: 23 cm
Width: 19 cm
Depth: 10 cm



WAND Bluetooth and Wi-Fi Module
Height: 2 cm
Width: 5 cm
Depth: 5 cm

Compatible with:



Hydrawise Software
Page 112



ROAM Remote
Page 140
ROAM XL Remote
Page 141



Rain-Click Sensor
Page 146

X2 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3		
1 Model	2 Transformer	3 Plug
X2-4 = 4-station	00 = 120 VAC	(blank) = American plug
X2-6 = 6-station	01 = 230 VAC	E = European connections, no plug
X2-8 = 8-station		A = Australian plug
X2-14 = 14-station		

Examples:
X2-1401-E = 14-station controller, 230 VAC internal transformer with no plug
X2-1401-A = 14-station controller, 230 VAC internal transformer with Australian plug

WAND MODULE	
Model	Description
WAND	Bluetooth and Wi-Fi Module for Hydrawise Irrigation Management Platform



Smart WaterMark
Recognised as a responsible water-saving tool when used with the WAND Module

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG Inc. and any use of such marks by Hunter Industries is under licence. Amazon Alexa is a trademark of Amazon.com Inc. or its affiliates. Control4 is a registered trademark of Control4 Corporation in the United States and/or other countries. HomeSeer is a trademark of HomeSeer Technologies LLC.