



- 01 **Water Saving:** Saves up to 30% over traditional nozzles
- 02 **Reliable:** Slim but durable body with double filtration
- 03 **Versatile:** Choose from 6 different models with factory-installed MP Rotators®

ECO ROTATOR®

Maximum Efficiency, Flexibility, and Performance

The Eco Rotator allows water savings of up to 30% over traditional sprays with its pre-installed MP Rotator featuring multi-stream, multi-trajectory technology. Rather than simply spraying water onto landscapes, the MP Rotator delivers streams of water at a slower rate that soils can absorb, significantly reducing runoff. The Eco Rotator's pop-up spray body has a reliable two-piece ratchet, durable cap, and large filter screen with double filtration, all in a compact 10-centimeter size, just right for a variety of applications.

ECO ROTATOR PERFORMANCE DATA

ECO-04 MP1000

Radius: 2.5 to 4.5 m
Adjustable Arc and Full-Circle
● Maroon: 90° to 210°
● Olive: 360°

ECO-04 MP2000

Radius: 4.0 to 6.4 m
Adjustable Arc and Full-Circle
● Black: 90° to 210°
● Red: 360°

ECO-04 MP3000

Radius: 6.7 to 9.1 m
Adjustable Arc and Full-Circle
● Blue: 90° to 210°
● Grey: 360°

Arc	Pressure		Radius		Flow		Precip mm/hr		Radius		Flow		Precip mm/hr		Radius		Flow		Precip mm/hr																																																																																																							
	bar	kPa	m	m ³ /hr	l/min	■	▲	m	m ³ /hr	l/min	■	▲	m	m ³ /hr	l/min	■	▲	m	m ³ /hr	l/min	■	▲																																																																																																				
90° ●	1.7	170	--	--	--	--	--	5.2	0.07	1.18	11	12	7.6	0.16	2.63	11	13	2.0	200	3.7	0.04	0.61	11	12	5.5	0.07	1.23	10	11	8.2	0.17	2.77	10	11	2.5	250	4.0	0.04	0.68	10	12	5.8	0.09	1.43	10	12	8.5	0.19	3.08	10	12	2.8	280	4.1	0.04	0.70	10	11	6.1	0.09	1.52	10	11	9.1	0.20	3.25	9	11	3.0	300	4.3	0.04	0.73	10	11	6.4	0.09	1.57	9	10	9.1	0.20	3.38	10	11	3.5	350	4.4	0.05	0.78	10	11	6.4	0.10	1.68	10	11	9.1	0.22	3.67	11	12	3.8	380	4.5	0.05	0.81	9	11	6.4	0.11	1.77	11	12	9.1	0.23	3.80	11	13			
	180° ●	1.7	170	--	--	--	--	--	4.9	0.13	2.22	11	12	7.6	0.32	5.48	11	13	2.0	200	3.7	0.07	1.20	11	12	5.2	0.14	2.35	11	12	8.2	0.35	5.88	10	12	2.5	250	4.0	0.08	1.35	10	12	5.5	0.16	2.67	11	12	8.5	0.40	6.55	11	12	2.8	280	4.1	0.08	1.40	10	11	5.8	0.17	2.80	10	12	9.1	0.41	6.88	10	11	3.0	300	4.3	0.09	1.46	10	11	6.1	0.17	2.90	10	11	9.1	0.43	7.18	10	12	3.5	350	4.4	0.09	1.56	10	11	6.4	0.19	3.15	9	10	9.1	0.47	7.77	11	13	3.8	380	4.5	0.10	1.62	9	11	6.4	0.19	3.22	9	11	9.1	0.45	8.02	12	13		
		210° ●	1.7	170	--	--	--	--	--	4.9	0.16	2.58	11	12	7.6	0.38	6.40	11	13	2.0	200	3.7	0.09	1.41	11	13	5.2	0.17	2.75	11	13	8.2	0.41	6.85	10	12	2.5	250	4.0	0.10	1.58	10	12	5.5	0.19	3.08	10	12	8.5	0.46	7.65	11	12	2.8	280	4.1	0.10	1.63	10	11	5.8	0.20	3.25	10	12	9.1	0.48	8.02	10	11	3.0	300	4.3	0.10	1.71	10	11	6.1	0.21	3.42	10	11	9.1	0.50	8.37	10	12	3.5	350	4.4	0.11	1.82	10	11	6.4	0.22	3.70	9	10	9.1	0.54	9.03	11	13	3.8	380	4.5	0.11	1.89	9	11	6.4	0.23	3.80	10	11	9.1	0.56	9.37	12	13	
			360° ●	1.7	170	--	--	--	--	--	4.9	0.27	4.42	11	12	7.6	0.66	10.98	11	13	2.0	200	3.7	0.14	2.40	12	14	5.2	0.28	4.72	11	13	8.2	0.70	11.72	10	12	2.5	250	4.0	0.16	2.69	10	12	5.5	0.32	5.28	10	12	8.5	0.79	13.10	11	12	2.8	280	4.1	0.17	2.81	10	12	5.8	0.33	5.55	10	12	9.1	0.83	13.75	10	11	3.0	300	4.3	0.18	2.94	10	11	6.1	0.35	5.80	10	11	9.1	0.87	14.37	10	12	3.5	350	4.4	0.19	3.17	10	11	6.4	0.37	6.25	9	10	9.1	0.93	15.52	11	13	3.8	380	4.5	0.20	3.25	10	11	6.4	0.38	6.40	9	10	9.1	0.96	16.07	12	13

Bold = Recommended pressure

ECO ROTATOR

Model	Description
ECO-04 - 1090	10 cm pop-up, 2.5 to 4.5 m radius, adjustable from 90° to 210°
ECO-04 - 10360	10 cm pop-up, 2.5 to 4.5 m radius, 360°
ECO-04 - 2090	10 cm pop-up, 4.0 to 6.4 m radius, adjustable from 90° to 210°
ECO-04 - 20360	10 cm pop-up, 4.0 to 6.4 m radius, 360°
ECO-04 - 3090	10 cm pop-up, 6.7 to 9.1 m radius, adjustable from 90° to 210°
ECO-04 - 30360	10 cm pop-up, 6.7 to 9.1 m radius, 360°



Multiple rotating streams provide even coverage and wind resistance with a matched application rate at any radius or arc

Strong body cap for long life and easy installation

Double filtration for double debris protection

Two-piece ratchet for dependable and reliable performance

Eco Rotator
Overall height: 19 cm
Exposed diameter: 3 cm
Inlet size: ½"

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gregory R. Hunter
Gregory R. Hunter, President of Hunter Industries

